



HARDWARE FEATURES

- Automated turntable to fixture parts to ensure held in place during operation
- Clean In Place (CIP) system when finishing is complete, nozzles rinse parts in the same chamber
- Hinged electrical panel design allows for easy access for maintaining controls and motor
- Fully welded stainless steel chamber provides corrosion resistance and operator safety
- Pumping system with easy maintenance
- Casters for easy installation / relocation

RESULTING IN...

- + Preserving fine feature part detail
- + Fast cycle times
- + Automated finishing

SOFTWARE FEATURES

- Patent-pending AUTOMAT3D™ platform
- · Proprietary Agitation Algorithms
- Variable temperature up to 130°F (54°C)
- · Intelligent cycle times
- · Customizable settings
- · One-touch repeatability with recipes storage
- · Media Seperation Sequence
- Pre-programmed preventative maintenance schedules

RESULTING IN...

- + Minimal operator intervention
- + Precision machine programming
- + Consistency and repeatability



PRODUCT SPECIFICATIONS

SIZE & WEIGHT SPECIFICATIONS

Envelope:

Both Nozzles: 15" L x 15" W x 12" H

(38 cm x 38 cm x 30.4 cm)

Top Nozzle Only: 15" L x 15" W x 15" H

(38 cm x 38 cm x 38 cm)

Machine Footprint (Chamber Door Closed):

69.5" L × 37" W × 94" H (177 cm x 94 cm x 239 cm)

Machine Footprint (Chamber Door Open):

69.5" L × 67" W × 94" H

(177 cm x 170 cm x 239 cm)

Approx. Weight: 2180 lbs. (989 kg) empty;
2350 lbs. (1066 kg) full

ELECTRICAL SPECIFICATIONS

· Voltage: 480V 3 Phase

· Amperage: 25A

· Connector: HBLS430C7W

**other voltage options available

CONSUMABLES

- · PLM-001-DUO detergent
- ZB-CBM, MB-CBM, ZS-CBM425, AS-ALO and PS-SS suspended solids

SAFETY FEATURES

- Emergency stop
- External LED lighted chamber
- · Sealed chamber with door safety lock
- · Compliant with all OSHA regulations
- · (€

MATERIALS AND TECHNOLOGIES



DMLS · SLM · DED

POSTPROCESS TECHNOLOGIES INC.

2495 Main Street, Suite 615, Buffalo NY 14214 USA info@postprocess.com +1.866.430.5354

POSTPROCESS TECHNOLOGIES INTERNATIONAL

49 Impasse du Hameau, 06250 Mougins, France +33 (0)4 22 32 68 13