

## RSPro 1400


This innovative dual laser-dual scanning additive manufacturing system is perfectly suited for the industrial production of large, high quality finished parts as well as mass part production.



- Automatic calibration set-up ensures accuracy.
- High precision parts with no visible joint lines.
- Carbon fiber reinforced recoater system ensures non-deformation across 1400 mm length.
- Granite recoater frame enhances stability.
- Open design for freedom of choice of materials and software.

## RSPro 1400

Technology Type	Stereolithography (SLA)	Network Type and Protocol	Ethernet, IEEE 802.3 using TCP/IP and NFS
Build Envelope Capacity	1400 × 700 × 500 mm	Electrical Requirements	200-240 VAC, 50/60 Hz, Single phase
Accuracy	L < 100 mm: ±0.2 mm L ≥ 100 mm: ±0.2% × L	Rated Power	3.9 kVA
Layer Thickness	0.1 - 0.25 mm	Systems Control	Closed-loop
Recoater Frame	Granite	Temperature Range	72–79 °F (22–26 °C)
Laser	Solid-state frequency tripled Nd: YVO <sub>4</sub>	Maximum Change Rate	1 °C/hour
Beam Size	0.12 - 0.2 mm	Relative Humidity	< 40% non-condensing
Wavelength	355 nm	Machine Size (W x D x H)	2882 × 1952 × 2395 mm
Scanning Speed	6 ~ 10 m/s	Machine Weight	1907 kg
Controlling Software	UnionTech™ RSCON	Initial Resin Weight	940 kg
Data Preparation Software	Polydevs	Resin Tank	Fixed
Operation System	Windows 10	Processing and Finishing	Post-Curing Unit (optional)
Input Data File Format	STL	Warranty	12 months



**UnionTech**

**UnionTech 3D LTD**

Room 102, Unit 40, 258 Xinzhuang Rd, Shanghai, 201612, China  
mkt@uniontech3d.com Tel: +86-021-64978786  
www.uniontech3d.com

**UnionTech GmbH**

Regus Berliner Carree, Berliner Allee 47,  
64295 Darmstadt, Germany  
Tel: +49 (0) 6151-2776067  
info@uniontech3d.de  
www.uniontech3d.de

**UnionTech Russia**

4, 2nd Roschinskay str., office 314,  
115191, Moscow, Russia  
Tel: +79100025900  
info@uniontech3d.ru  
www.uniontech3d.ru